

Mixing Power Amplifier

Features

- High/Low Impedance Outputs(8Ω/50,70,100V)
- Priority Function for Emergency Call
- Separate Bass & Treble Control
- AC Mains or DC 24V Operation

MPA-2400 / MPA-3600



19" 3U Standard Rack-Mount

- **MPA-2400** : 240W(rms)
- **MPA-3600** : 360W(rms)
- 4 Zone Speaker Selector Outputs
- Balance & Unbalance Microphone Inputs
- 5 Microphone Inputs with Individual Volume Control
- Aux Input (CD/TUNER/MP3) Selectable
- Dimensions : 482W x 142H x 355Dmm

MPA-1200



19" 3U Standard Rack-Mount

- Power : 120W(rms)
- 4 Zone Speaker Selector Outputs
- Balance & Unbalance Microphone Inputs
- 5 Microphone Inputs with Individual Volume Control
- Aux Input (CD/TUNER/MP3) Selectable
- Dimensions : 482W x 142H x 327Dmm

MPA-600 / MPA-900



- **MPA-600** : 60W(rms)
- **MPA-900** : 90W(rms)
- 4 Zone Speaker Selector Outputs
- Balance & Unbalance Microphone Inputs
- 5 Microphone Inputs with Individual Volume Control
- Aux Input (CD/TUNER/MP3) Selectable
- Dimensions : 440W x 94H x 316Dmm

MPA-400



- Power : 40W(rms)
- 4 Microphone & 1 Aux Input
- Built-in Condenser Microphone (Mic. 1)
- Dimensions : 310W x 88H x 250Dmm

Mini Amplifier

MMA-10 Class-D



- 10W Mini Amplifier (6Wrms)
- Power Input : DC 12~24V
- 2 Mic Inputs (Included Aux & MP3)
- Speaker Output : 4Ω ~ 8Ω
- Dimensions : 86 x 86mm

MA-20 20Wmax Classroom Amplifier



- 2 Microphone & 1 Aux Input
- Built-in Priority Function (Mic. 1)
- Low Impedance Output : 4Ω ~ 8Ω
- Dynamic / Condenser Mic
- Power Input : AC 220V
- Dimensions : 292W x 190H x 65Dmm

MA-12 12Wmax Mini Amplifier



- 2 Microphone & 1 Aux Input
- Low Impedance Output : 4Ω ~ 8Ω
- Power Input : AC 230V / DC12~24V
- Dimensions : 168W x 45H x 140Dmm

MA-22 20Wmax Mini Amplifier



- 2 Microphone & 1 Aux Input
- Low Impedance Output : 4Ω ~ 8Ω
- Power Input : AC 115V / AC 230V
- Dimensions : 220W x 55H x 160Dmm